

**TRANWO**<sup>TM</sup>  
Smart Wireless Video

# GigaAir<sup>TM</sup> VMi110

Easy iCAM Remote Wireless  
Video Surveillance Camera



Wi-Fi

Wi-Fi



30  
seconds

Easy & Quick  
Setup



Local / Remote  
View Selection

Local / Remote  
View Selection



Voice Activation



Snap Shot



Multi-user



Night Vision

## Setup

- Easy and quick setup in 30 seconds without the use of ethernet cable or QR Code

## Operation

- Easy to use as a plug & play device

## Connectivity

- As quick & easy as Wi-Fi Direct
- Automatically switch local view/remote view by one selection

## Privacy

- ID protection to secure privacy

## Alert

- Voice activation with alert notification when playing game or receiving mails

## System

- Allow multiple users to monitor simultaneously
- Snap shot



### Local View



Easy iCAM Smart Phone, Tablet

### Internet View



Easy iCAM Wireless AP/Router Smart Phone, Tablet



\* iPhone, iPad are trademarks of Apple Inc., registered in the U.S. and other countries.  
\* Google Play is a trademark of Google Inc.

[www.tranwo.com](http://www.tranwo.com)

**TRANWO Technology Corp.**  
No.236, Sec. 3, Huanbei Rd., Jubei City, Hsinchu County 30265, Taiwan  
TEL: +886-3-553-5326 FAX: +886-3-553-5283  
EMAIL: sales@tranwo.com [www.tranwo.com](http://www.tranwo.com)



Use the *Easy iCAM* to  
find everything  
you most concern.

**Specifications:**

Wireless	Wireless standard	IEEE 802.11b/g/n	
	Frequency	2.4 GHz ISM band	
	Channel	14 channels	
	RF output power	11b >= 16.5 dBm	
		11g >= 14.5 dBm	
		11n >= 14 dBm	
Spread spectrum	DSSS		
Modulation	DBPSK, DQPSK, CCK and OFDM		
Video	Type	1/6" color CMOS	
	Effective pixel (H/V)	H: 640 ; V: 480	
	Image resolution	VGA	
	Lens focus	1.5m ~ ∞	
	View angle U/D/R/L(TYP)	17/17/21.5/21.5 deg	
	Video compression	MJPEG (Motion JPEG)	
	Video streaming	MJPEG streaming	
	Frame rate	>=15 fps in normal condition	
	Auto white balance	Yes	
Audio	Audio input	One-way audio with built-in MIC	
	Sampling rate	8K, 16 bits	
	Sampling compression	PCM	
Night vision	Light sensor	Yes	
	IR LED	8pcs, 850nm wavelength	
	Night vision activation	4 Lux activation	
	Night vision range	Clearly see face in 1.5m	
Day & Night	Day & Night	IR-Cut	
	Software	iOS	Support iPhone, iPad
Android		Android 2.1 or up	
System	Security	WPA2-PSK(AES, TKIP),	
		WPA-PSK(AES, TKIP), 128/64 bit WEP	
	Voice detection alarm function	Yes	
	Display resolution	VGA(640x480), QVGA(320x240)	
	Still image capture	Yes	
	AP client	Support AP-client	
	Power supply	Adapter: 6V, 800mA	
	Dimension	85.1(W)x85.1(D)x106.3(H)mm	
	Operating temperature range	0°C~40°C	
Operating humidity range	40~90%RH		
Storage Temperature range	-20°C~60°C		

Specifications are subject to change without prior notice.



Kids



Home/Office



Seniors



Pets