

TRANWO™
Smart Wireless Video

GigaAir™ VMi111A

Easy iCAM Remote Wireless
Video Surveillance Camera



Wi-Fi



Easy & Quick Setup



Local / Remote View Selection



Voice Activation



Snap Shot



Multi-user



Night Vision

Setup

- Easy and quick setup in 30 seconds without the use of ethernet cable or QR Code

Operation

- Easy to use as a plug & play device

Connectivity

- As quick & easy as Wi-Fi Direct
- Automatically switch local view/remote view by one selection

Privacy

- ID protection to secure privacy

Alert

- Voice activation with alert notification when playing game or receiving mails

System

- Allow multiple users to monitor simultaneously
- Snap shot




Local View



Easy iCAM Smart Phone, Tablet

Internet View




Easy iCAM Wireless AP/Router Smart Phone, Tablet



* iPhone, iPad are trademarks of Apple Inc., registered in the U.S. and other countries.
* Google Play is a trademark of Google Inc.

www.tranwo.com

TRANWO Technology Corp.
No.236, Sec. 3, Huanbei Rd., Jubei City, Hsinchu County 30265, Taiwan
TEL: +886-3-553-5326 FAX: +886-3-553-5283
EMAIL: sales@tranwo.com www.tranwo.com



Specifications:

Wireless	Wireless standard	IEEE 802.11b/g/n
	Frequency	2.4 GHz ISM band
	Channel	14 channels
	RF output power	11b >= 16.5 dBm
		11g >= 14.5 dBm
11n >= 14 dBm		
Spread spectrum	DSSS	
Modulation	DBPSK, DQPSK, CCK and OFDM	
Video	Type	1/6" color CMOS
	Effective pixel (H/V)	H: 640 ; V: 480
	Image resolution	VGA
	Lens focus	1.5m ~ ∞
	View angle U/D/R/L(TYP)	17/17/21.5/21.5 deg
	Video compression	MJPEG (Motion JPEG)
	Video streaming	MJPEG streaming
	Frame rate	>=15 fps in normal condition
	Auto white balance	Yes
Audio	Audio input	One-way audio with built-in MIC
	Sampling rate	8K, 16 bits
	Sampling compression	PCM
Night vision	Light sensor	Yes
	IR LED	8pcs, 850nm wavelength
	Night vision activation	4 Lux activation
	Night vision range	Clearly see face in 1.5m
Day & Night	Day & Night	IR-Cut
	Software	iOS
Android		Android 2.1 or up
System	Security	WPA2-PSK(AES, TKIP),
		WPA-PSK(AES, TKIP), 128/64 bit WEP
	Voice detection alarm function	Yes
	Display resolution	VGA(640x480), QVGA(320x240)
	Still image capture	Yes
	AP client	Support AP-client
	Power supply	Adapter: 6V, 800mA
	Dimension	80(W)x80(D)x117.2(H)mm
Operating temperature range	0°C~40°C	
Operating humidity range	40~90%RH	
Storage Temperature range	-20°C~60°C	

Specifications are subject to change without prior notice.



Seniors



Home/Office



Kids



Pets