

GigaAirTM VMi112

Easy iCAM Remote Wireless
Video Surveillance Camera



Setup

- Easy and quick setup in 30 seconds without the use of ethernet cable or QR Code

Operation

- Easy to use as a plug & play device

Connectivity

- As quick & easy as Wi-Fi Direct
- Automatically switch local view/remote view by one selection

Privacy

- ID protection to secure privacy

Alert

- Voice activation with alert notification when playing game or receiving mails

System

- Allow multiple users to monitor simultaneously
- Snap shot
- Temperature sensor



* iPhone, iPad are trademarks of Apple Inc., registered in the U.S. and other countries.
* Google Play is a trademark of Google Inc.



Specifications:

Wireless	Wireless standard	IEEE 802.11b/g/n	
	Frequency	2.4 GHz ISM band	
	Channel	14 channels	
	RF output power	11b >= 16.5 dBm	
		11g >= 14.5 dBm	
		11n >= 14 dBm	
	RF sensitivity @ 10%PER	150M: -65dBm; 130M: -68dBm; 108M: -68dBm 54M: -72dBm; 11M: -85dBm; 6M: -88dBm	
Spread spectrum	DSSS		
Modulation	DBPSK, DQPSK, CCK and OFDM		
Video	Type	1/6" color CMOS	
	Effective pixel (H/V)	H: 640 ; V: 480	
	Image resolution	VGA	
	Lens focus	1.5m ~ ∞	
	View angle U/D/R/L(TYP)	17/17/21.5/21.5 deg	
	Video compression	MJPEG (Motion JPEG)	
	Video streaming	MJPEG streaming	
Frame rate	>= 15 fps in normal condition		
Auto white balance	Yes		
Audio	Audio input	One-way audio with built-in MIC	
	Sampling rate	8K, 16 bits	
	Sampling compression	PCM	
Night vision	Light sensor	Yes	
	IR LED	8pcs, 850nm wavelength	
	Night vision activation	4 Lux activation	
	Night vision range	Clearly see face in 1.5m	
Day & Night	IR-Cut		
Software	iOS	Support iPhone, iPad	
	Android	Android 2.1 or up	
System	Security	WPA2-PSK(AES,TKIP), WPA-PSK(AES,TKIP),128/64 bit WEP	
	Temperature sensor	Yes	
	Voice detection alarm function	Yes	
	Display resolution	VGA(640x480),QVGA(320X240)	
	Still image capture	Yes	
	AP client	Support AP-client	
	Power supply	Adapter: 6V,800mA	
	Dimension	85(W)x100(D)x110(H)mm	
	Operating temperature range	0°C~40°C	
	Operating humidity range	40~90%RH	
Storage Temperature range	-20°C~60°C		


Specifications are subject to change without prior notice.



Kids



Home/Office



Seniors



Pets